

SPLIT PHASE BELT DRIVE MOTORS

eMotortek™

Features:

- Continuous Duty
- 40°C Design
- Reversible
- Resilient Base has 48 & 56 Frame Mounting Holes
- Motors with (X) have Extended Thru-Bolts
- Single & Dual Voltage
- Automatic Overload
- Class B Insulation
- Sleeve or Ball Bearing
- Open Drip-Proof
- Shaft Adapter for 5/8" Shaft and Keyway Included



Stock No.	HP	Volts	Amps.	Service Factor	RPM	"A"	Shaft Dimension	Bearing	Cross Reference
SS933	1/4	115	4.8	1.35	1725	6-1/2"	1/2" X 1-1/2"	Sleeve	GF2024, 4701, B206, H701
SS933D (X)	1/4	115 / 208 – 230	4.6 / 2.3	1.35	1725	6-7/8"	1/2" X 1-7/8"	Ball	BF2024, 4680, PD6002
SS934	1/3	115	6.6	1.35	1725	6-3/4"	1/2" X 1-1/2"	Sleeve	GF2034, 4706, B207, H711
SS934B	1/3	115	6.6	1.35	1725	6-3/4"	1/2" X 1-1/2"	Ball	RB2034, H700, B305, 841, 8100
SS934D (X)	1/3	115 / 208 – 230	6.6 / 3.1	1.35	1725	6-7/8"	1/2" X 1-7/8"	Ball	BF2034, PD6004
SS935	1/2	115	7.6	1.25	1725	7-3/4"	1/2" X 1-1/2"	Sleeve	GF2054, B208, 4708
SS935B	1/2	115	7.6	1.25	1725	7-3/4"	1/2" X 1-1/2"	Ball	H703, B307, 1542C, 8200
SS935D (X)	1/2	115 / 208 – 230	7.6 / 3.8	1.25	1725	7-7/8"	1/2" X 1-7/8"	Ball	BF2054, PD6006
SS936D (X)	3/4	115 / 208 – 230	11.6 / 5.8	1.25	1725	9-5/8"	5/8" X 1-7/8"	Ball	F680

