


PMDC MOTORS TEFC & TENV CONSTRUCTION

eMotortek™

Features:

- Class "F" Insulation
- Permanent Magnet
- UL Listed & CSA Approved
- Continuous Duty
- No Overload
- 20:1 C.T. Speed Range
- 40°C Ambient
- Removable Rigid Base
- 1.00 S.F.
- Ball Bearing
- Reversible
- 1725 RPM



90 VDC

HP	Frame	Stock No.	Amps	"C"	Enclosure	Brush Repl.	Cross Reference
1/4	56C	DC500	2.6	10.25"	TENV	BR56	D039, DC119
	56C	DC500A	2.6	10.75"	TEFC	BR56	D038, DC118, 098002.0
1/3	56C	DC501	3.5	10.25"	TENV	BR56	D040
1/2	56C	DC502	5	12.25"	TEFC	BR56	D041, 098000.00
3/4	56C	DC503	7.6	13.75"	TEFC	BR56	D043, DC123, 098032.00
1	56C	DC504	10	14.75"	TEFC	BR56	D044, 108022.00

180 VDC


HP	Frame	Stock No.	Amps	"C"	Enclosure	Brush Repl.	Cross Reference
1/2	56C	DC512	2.5	12.25"	TEFC	BR56	D060, 098008.00
3/4	56C	DC513	3.8	13.75"	TEFC	BR56	D061, 098069.00
1	56C	DC514	5	14.75"	TEFC	BR56	D062, DC132 108023.00
1.5	143/5TC	DC515	8	15.50"	TEFC	BR140	D080, DC142, 128000.00
2	143/5TC	DC516	9.5	18.75"	TEFC	BR140	D081, 128010.00
3	143/5TC	DC517	14	19.25"	TEFC	BR140	D082, DC144

PMDC MOTORS TEFC & TENV CONSTRUCTION

eMotortek™

Features:

- Class "F" Insulation
- Permanent Magnet
- UL Listed & CSA Approved
- Continuous Duty
- No Overload
- 20:1 C.T. Speed Range
- 40°C Ambient
- Removable Rigid Base
- 1.00 S.F.
- Ball Bearing
- Reversible
- 1725 RPM



12/24 VDC

HP	Volts	Frame	Stock No.	Amps	"C"	Enclosure	Brush Repl.	Cross Reference
1/2	12	56C	DC522	40	12.25"	TEFC	BR56	108047
	24	56C	DC532	20	12.75"	TEFC	BR56	108051
1	12	56C	DC524	80	12.25"	TEFC	BR56	108322
	24	56C	DC534	40	14.75"	TEFC	BR56	108053

*KB Drives Available.

Please Follow the Link for KB Products: <https://universalmotors.ca/kb>