


GENERAL PURPOSE MOTORS SINGLE AND THREE PHASE OPEN DRIP PROOF – T FRAME

eMotortek™

Features:

- Rolled Steel Construction
- Class "F" Insulation
- UL Listed & CSA Approved
- Continuous Duty
- Reversible
- Dual Mounting Holes in Base
- Inverter Duty 10:1 VT / 2:1 CT
- 40°C Ambient
- Rigid Base
- No Overload
- 1.15 S.F.
- 60 Hz.
- Ball Bearing



575 Volts (3 Phase)

HP	RPM	Frame	Stock No.	Amps	"C"	Cross Reference
1	1800	143/5T	EMO654	1.4	11.63"	ORP654, D1P2G
1.5	1800	143/5T	EMO655	1.8	11.63"	ORP655, D32P2G
2	1800	143/5T	EMO656	2.3	11.63"	ORP656, D2P2G
3	1800	182/4T	EMO657	3.3	13.81"	ORP657, D3P2G
5	1800	182/4T	EMO658	5.4	13.81"	ORP658, D5P2G
7.5	1800	213/5T	EMO659	7.8	16.91"	ORP659, D7P2G
10	1800	213/5T	EMO65A	10.5	16.91"	ORP65A, D10P2G
15	1800	254/6T	EMO65B	15.5	20.72"	ORP65B, D15P2G
20	1800	254/6T	EMO65C	20.8	20.72"	ORP65C, D20P2G

GENERAL PURPOSE MOTORS SINGLE AND THREE PHASE OPEN DRIP PROOF – T FRAME

230 / 460 Volts (3 Phase)

HP	RPM	Frame	Stock No.	Amps	"C"	Cross Reference
1	1800	143/5T	EMO674	3.2 / 1.6	11.63"	ORP674, D1P2D
1.5	1800	143/5T	EMO675	4.5 / 2.2	11.63"	ORP675, D32P2D
2	1800	143/5T	EMO676	5.9 / 2.9	11.63"	ORP676, D2P2D
3	1800	182/4T	EMO677	8.0 / 4.0	13.81"	ORP677, D3P2D
5	1800	182/4T	EMO678	13.2 / 6.6	13.81"	ORP678, D5P2D
7.5	1800	213/5T	EMO679	19.0 / 9.5	16.91"	ORP679, D7P2D
10	1800	213/5T	EMO67A	25.0 / 12.5	16.91"	ORP67A, D10P2D

230 Volts (1 Phase)

HP	RPM	Frame	Stock No.	Amps	"C"	Cross Reference
3	1800	182/4T	EMO547	11.9	15.5"	OR547, V201
5	1800	182/4T	EMO548	20.0	15.75"	OR548, V205

C-Face Kit

Stock No.	Frame	Fits
COR14	143/5T	EMO654 / EMO655 / EMO656 / EMO674 / EMO675 / EMO676
COR18	182/4T	EMO657 / EMO658 / EMO677 / EMO678
COR21	213/5T	EMO659 / EMO65A / EMO679 / EMO67A