


GENERAL PURPOSE & FARM DUTY T FRAME MOTORS SINGLE PHASE – ROLLED STEEL TEFC

eMotortek™

Features:

- Rolled Steel Construction
- Class "F" Insulation
- UL Listed & CSA Approved
- Continuous Duty
- Reversible
- Ball Bearing
- High Efficiency Capacitor Start/Run Design
- 40°C Ambient
- Rigid Base
- No Overload
- 1.15 S.F.
- 60 Hz.
- C Face Kits Available



HP	RPM	Volts	Frame	Stock #	Amps	"C"	Cross Reference
2	1800	115 / 230	143/5T	EMF176	16.5 / 8.3	14.22"	FD176, Z128
3	3600	230	182T	EMF127	14.0	16.72"	FD127
	1800	230	184T	EMF177	14.5	16.72"	FD177, K205, Z120A
5	3600	230	184T	EMF128	20.0	16.72"	FD128
	1800	230	184T	EMF178	20.1	18.13"	FD178, K208
7.5	3600	230	213T	EMF129	29.0	16.72"	FD129
	1800	230	215T	EMF179	30.0	20.31"	FD179, K311, Z122, MTR-754FDH
10	3600	230	215T	EMF12A	39.0	20.31"	FD12A
	1800	230	215T	EMF17A	38.2	20.31"	FD17A, K312, MTR-1004FD