


GENERAL PURPOSE & FARM DUTY SINGLE PHASE - C FACE MOTORS

eMotortek™

Features:

- Rolled Steel Construction
- Class "B" Insulation
- UL Listed & CSA Approved
- Continuous Duty
- 40°C Ambient
- Removable Rigid Base
- Manual Overload
- High Efficiency Capacitor Start/Run Design
- 1.15 S.F.
- 60 Hz.
- Reversible
- Ball Bearings



HP	RPM	Volts	Frame	Stock No.	Amps	"C"	Cross Reference
1/3	3600	115 / 230	56C	EMF141C	4.7 / 2.5	12.0"	FD141C, MTR-132FDCH, FDR.332C-C-01
	1800	115 / 230	56C	EMF161C	4.3 / 2.2	12.2"	FD161C, MTR-134FDCH, FDR334C-C-01
1/2	3600	115 / 230	56C	EMF142C	5.9 / 3.1	12.0"	FD142C, MTR-122FDCH, FDR.502C-C-01
	1800	115 / 230	56C	EMF162C	5.8 / 3.0	12.0"	FD162C, MTR-124FDCH, FDR.501C-C-01
3/4	3600	115 / 230	56C	EMF143C	8.1 / 4.2	12.0"	FD143C, MTR-342FDCH, FDR.752C-C-01
	1800	115 / 230	56C	EMF163C	8.1 / 4.2	12.0"	FD163C, MTR344FDCH, FDR.754C-C-01
1	3600	115 / 230	56C	EMF144C	8.3 / 4.4	12.0"	FD144C, MTR-102FDCH
	1800	115 / 230	56C	EMF164C	9.2 / 5.0	12.0"	FD164C, MTR-104FDCH
1.5	3600	115 / 230	56C	EMF145C	14.0 / 7.0	12.0"	FD145C, MTR-152FDCH
	1800	115 / 230	56C	EMF165C	13.3 / 7.1	12.6"	FD165C, MTR-154FDCH
2	3600	115 / 230	56HC	EMF146C	16.2 / 8.4	13.0"	FD146C, MTR-202FDCH, FDR0022C-C-01
	1800	115 / 230	56HC	EMF166C	16.5 / 9.0	14.2"	FD166C, MTR-204FDCH, FDR0024C-C-01
3	3600	115 / 230	56HC	EMF147C	13.1 - 12.3	14.6"	FD147C
5	3600	208 - 230	56HC	EMF138C	20.7 - 18.5	12.0"	FD138C