


GENERAL PURPOSE 3 PHASE OPEN DRIP PROOF

eMotortek™

Features:

- Rolled Steel Construction
- Class "F" Insulation
- UL Listed & CSA Approved
- Continuous Duty
- Reversible
- Ball Bearings
- 40°C Ambient
- Rigid Base
- No Overload
- 1.15 S.F.
- 60 Hz.



230/460 Volts

HP	RPM	Frame	Stock No.	Amps	"C"	Cross Reference
1/2	1800	56	EMD682	2.2 / 1.1	10.75"	WD682
3/4	1800	56	EMD683	2.8 / 1.4	10.75"	WD683
1	1800	56	EMD684	3.6 / 1.8	10.75"	WD684
1.5	1800	56	EMD685	4.6 / 2.3	10.75"	WD685
2	1800	56	EMD686	5.8 / 2.9	10.75"	WD686

575 Volts

HP	RPM	Frame	Stock No.	Amps	"C"	Cross Reference
1/3	1800	56	EMD661	0.65	10.75"	WD661
1/2	1800	56	EMD662	0.87	10.75"	WD662
3/4	1800	56	EMD663	1.12	10.75"	WD663
1	1800	56	EMD664	1.4	10.75"	WD664
1.5	1800	56	EMD665	1.8	10.75"	WD665
2	1800	56	EMD666	2.3	10.75"	WD666