

"SQUARE DESIGN" REFRIGERATION MOTORS



Features:

- Shaded Pole
- Totally Enclosed Air Over
- Sleeve Bearing
- Foot Mounting or 3 Tapped Holes on Opposite Shaft End
- Class B Insulation
- 21-23" Leads with Ring Terminals
- Thermally Protected
- Counterclockwise Shaft End



Stock No.	Watts	Volts	RPM	Amps.	"A"	Shaft Dimensions
4W115	4	115	1550	0.36	2.30"	Hubless X 0.49"
6W115	6	115	1550	0.41	2.30"	Hubless X 0.49"
9W115	9	115	1550	0.58	2.50"	Hubless X 0.63"
9W230	9	230	1550	0.35	2.50"	Hubless X 0.63"
16W115	16	115	1550	0.89	2.80"	Hubless X 0.63"
16W230	16	230	1550	0.5	2.80"	Hubless X 0.63"
34W115	34	115	1550	1.6	3.50"	Hubless X 0.72"
34W230	34	230	1550	0.8	3.50"	Hubless X 0.72"
RMT0004*	34	115	1550	1.6	3.50"	Hubless X 1.16"
RMT0005*	34	230	1550	0.8	3.50"	Hubless X 1.16"

(*) 2 Pin Lyall Plug

